



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 1 of 16

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Montageschaum LORENCIC LO-FOAM 1K 750ml

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Foam

### Uses advised against

Any non-intended use.

### 1.3. Details of the supplier of the safety data sheet

Company name: Lorencic GmbH Nfg. & Co KG

Street: Puchstraße 208
Place: A-8055 Graz

Telephone: +43 (0) 316 / 47 25 64 32 Telefax: +43 (0) 316 / 47 25 64 78

Responsible Department: Dr. Gans-Eichler e-mail: info@tge-consult.de Chemieberatung GmbH Tel.: +49(0)2534 6441185

Otto-Hahn-Str. 36 www.tge-consult.de

D-48161 Münster

1.4. Emergency telephone Poison Control Centre Vienna: +43 (0) 1 406 43 43

number:

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

Hazard categories: Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Resp. Sens. 1 Respiratory or skin sensitisation: Skin Sens. 1

Carcinogenicity: Carc. 2 Reproductive toxicity: Lact.

Specific target organ toxicity - single exposure: STOT SE 3
Specific target organ toxicity - repeated exposure: STOT RE 2
Hazardous to the aquatic environment: Aquatic Acute 1
Hazardous to the aquatic environment: Aquatic Chronic 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.
Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction. Suspected of causing cancer.

May cause harm to breast-fed children.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

### 2.2. Label elements

# **GB CLP Regulation**



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 2 of 16

### Hazard components for labelling

alkanes, C14-17, chloro; chlorinated paraffins, C14-17

4,4'-methylenediphenyl diisocyanate, isomers and homologues

Signal word: Danger

Pictograms:









#### **Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P210 Keep away from heat. No Smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.

type A1 according to standard EN 14387) is used.

### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The mixture contains the following substances fulfilling the PBT-/vPvB criteria according to REACH Annex XIII: Decamethylcyclopentasiloxane, Dodecamethylcyclohexasiloxane, Octamethylcyclotetrasiloxane

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### **Hazardous components**

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	GHS Classification				
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17			40 - < 60 %	



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 3 of 16

	287-477-0	602-095-00-X	01-2119519269-33		
	Lact., Aquatic Acute 1, Aquatic Chr				
9016-87-9	4,4'-methylenediphenyl diisocyana	te, isomers and homologues		20 - < 40 %	
		615-005-01-6			
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373				
115-10-6	dimethyl ether				
	204-065-8	603-019-00-8	01-2119472128-37		
	Flam. Gas 1, Liquefied gas; H220 H280				
25322-69-4	Propane-1,2-diol, propoxylated				
	500-039-8				
	Acute Tox. 4; H302				

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity				
	Specific Conc.	Limits, M-factors and ATE					
85535-85-9	287-477-0	alkanes, C14-17, chloro; chlorinated paraffins, C14-17					
	mg/kg M acute	inhalation: LC50 = > 48,17 mg/l (vapours); dermal: LD50 = > 2800 mg/kg; oral: LD50 = > 4000 mg/kg M acute; H400: M=1 M chron.: H410: M=1					
9016-87-9		4,4'-methylenediphenyl diisocyanate, isomers and homologues	20 - < 40 %				
		60 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 g; oral: LD50 = > 2000 mg/kg					
25322-69-4	500-039-8	Propane-1,2-diol, propoxylated	5 - < 10 %				
	dermal: LD50 = >2000 mg/kg; oral: LD50 = 1000-2000 mg/kg						

### **Further Information**

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

## After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

Apply cortisone spray at early stage.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

# After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

### After ingestion

If swallowed, immediately drink: Water. Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting. Caution if victim vomits: Risk of aspiration! Call a physician immediately.





according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 4 of 16

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam. Atomized water.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Can be released in case of fire: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). Hydrogen chloride (HCI)

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains. In case of fire and/or explosion do not breathe fumes.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General measures

Ventilate affected area. Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

## For non-emergency personnel

Wear personal protection equipment (refer to section 8).

#### For emergency responders

Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. Eliminate leaks immediately. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

#### For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

# For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

# 6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

### **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 5 of 16

#### Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Wear suitable protective clothing. (See section 8.)

## Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Heating causes rise in pressure with risk of bursting.

#### Advice on general occupational hygiene

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Remove contaminated clothing immediatley and dispose off safely. Wash contaminated clothing prior to re-use. Used working clothes should not be worn outside the work area. Street clothing should be stored seperately from work clothing.

#### Further information on handling

General protection and hygiene measures: refer to chapter 8

# 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking. Provide adequate ventilation.

### Hints on joint storage

Do not store together with: Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. Self-reactive substances and mixtures. Organic peroxides. Radioactive substances.

Infectious substances.

### Further information on storage conditions

Recommended storage temperature: 10-30°C. Do not store at temperatures over: 50°C Note: Storage requirements for flammable aerosols.

### 7.3. Specific end use(s)

See section 1.

## **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
	,	-	0.07		STEL (15 min)	WEL

#### **DNEL/DMEL values**

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17						
Worker DNEL,	long-term	inhalation	systemic	6,7 mg/m³			
Worker DNEL, long-term		dermal	l •	47,9 mg/kg bw/day			
Consumer DNI	EL, long-term	inhalation	systemic	2 mg/m³			



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 6 of 16

Consumer DNEL, long-term	dermal	systemic	28,75 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,58 mg/kg bw/day
9016-87-9 4,4'-methylenediphenyl diisocyanate, isomers and homolo	gues		
Consumer DNEL, acute	inhalation	local	0,05 mg/m³
Consumer DNEL, long-term	inhalation	local	0,0025 mg/m³
Worker DNEL, acute	inhalation	local	0,1 mg/m³
Worker DNEL, long-term	inhalation	local	0,05 mg/m³
115-10-6 dimethyl ether			
Consumer DNEL, long-term	inhalation	systemic	471 mg/m³
Worker DNEL, long-term	inhalation	systemic	1894 mg/m³

### **PNEC** values

CAS No	Substance			
Environmenta	compartment	Value		
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17			
Freshwater		0,001 mg/l		
Marine water		0,0002 mg/l		
Freshwater se	diment	13 mg/kg		
Marine sedime	ent	2,6 mg/kg		
Secondary po	isoning	10 mg/kg		
Micro-organisi	ms in sewage treatment plants (STP)	80 mg/l		
Soil		11,9 mg/kg		
9016-87-9 4,4'-methylenediphenyl diisocyanate, isomers and homologues				
Freshwater	1 mg/l			
Freshwater (in	10 mg/l			
Marine water		0,1 mg/l		
Micro-organisi	ms in sewage treatment plants (STP)	1 mg/l		
Soil		1 mg/kg		
115-10-6	dimethyl ether			
Freshwater	•	0,155 mg/l		
Freshwater (in	termittent releases)	1,549 mg/l		
Marine water		0,016 mg/l		
Freshwater se	0,681 mg/kg			
Marine sedime	0,069 mg/kg			
Micro-organisi	ns in sewage treatment plants (STP)	160 mg/l		
Soil		0,045 mg/kg		

# 8.2. Exposure controls











### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection





according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 7 of 16

equipment.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

#### Individual protection measures, such as personal protective equipment

# Eye/face protection

Wear eye/face protection. BS/EN 166

#### Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material:

Butyl rubber. (0,5 mm)

Breakthrough time >480 min

penetration time (maximum wearing period): >160 min

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

#### Skin protection

Protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: Protective respiration apparatus not using surrounding air (breathing apparatus) (DIN EN 133).

Use only respiratory protection equipment with CE-symbol including four digit test number.

### **Environmental exposure controls**

Do not allow uncontrolled discharge of product into the environment.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: light yellow
Odour: characteristic

#### Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

-12 °C

boiling range:

Sublimation point: not determined
Softening point: not determined
Flash point: -83 °C

**Flammability** 

Gas: not determined

### **Explosive properties**

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Lower explosion limits: not determined Upper explosion limits: not determined



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 8 of 16

Auto-ignition temperature: not determined

**Self-ignition temperature** 

Gas: 460 °C

Decomposition temperature: not determined

**Oxidizing properties** 

none

pH-Value: not determined Viscosity / dynamic: not determined

(at 20 °C)

Viscosity / kinematic: not determined
Flow time: not determined
Water solubility: not determined

Solubility in other solvents

not determined

Vapour pressure: not determined

(at 20 °C)

Vapour pressure: 3000 hPa

(at 50 °C)

Density (at 20 °C): 0,982 g/cm³
Relative vapour density: not determined

9.2. Other information

Other safety characteristics

Solvent separation test:

Solvent content:

not determined

not determined

solid content:

not determined

Evaporation rate:

not determined

**Further Information** 

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

# 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

Refer to chapter 10.5.

#### 10.4. Conditions to avoid

Keep away from heat.

Ignition hazard.

Heating causes rise in pressure with risk of bursting.

### 10.5. Incompatible materials

Alcohol. amines. Ammonia. strong alkalis. Strong acid. Oxidizing agents, strong. Reducing agents, strong.

# 10.6. Hazardous decomposition products

Combustible. Vapours may form explosive mixtures with air. Can be released in case of fire: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). Hydrogen chloride (HCI)



according to UK REACH Regulation

## Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 9 of 16

#### **Further information**

In use, may form flammable/explosive vapour-air mixture.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in GB CLP Regulation

### Toxicocinetics, metabolism and distribution

No information available.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix tested**

	Dose	Species	Source
LD50, oral	13627,38 mg/kg		in analogy; MSDS extern.
LD50, dermal	> 2000 mg/kg		in analogy; MSDS extern.
LC50, inhalation (aerosol) (4 h)	47,69 mg/l		in analogy; MSDS extern.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
85535-85-9	alkanes, C14-17, chloro;	chlorinated pa	raffins, C1	4-17				
	oral	LD50 mg/kg	> 4000	Rat	Toxicol. Appl. Pharmacol. 54: 514-525 (1	Groups of at least 3 male and/or female		
	dermal	LD50 mg/kg	> 2800	Rat	ECHA Dossier	standard acute method		
	inhalation (1 h) vapour	LC50 mg/l	> 48,17	Rat	ECHA Dossier	standard acute method		
9016-87-9	4,4'-methylenediphenyl d	liisocyanate, is	somers and	l homologues				
	oral	LD50 mg/kg	> 2000					
	dermal	LD50 mg/kg	> 2000					
	inhalation (4 h) vapour	LC50	11 mg/l					
	inhalation aerosol	ATE	1,5 mg/l					
25322-69-4	Propane-1,2-diol, propoxy	ylated						
	oral	LD50 2000 mg/kg	1000-	Rat	MSDS extern.			
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier			

# Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

### Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (4,4'-methylenediphenyl diisocyanate, isomers and homologues)

May cause an allergic skin reaction. (4,4'-methylenediphenyl diisocyanate, isomers and homologues)

The product is: sensitizing.

People who suffer from skin sensitazion problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation.

### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (4,4'-methylenediphenyl diisocyanate, isomers and homologues)

May cause harm to breast-fed children. (alkanes, C14-17, chloro; chlorinated paraffins, C14-17)



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 10 of 16

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

alkanes, C14-17, chloro; chlorinated paraffins, C14-17:

In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative. Literature information: ECHA Dossier; Reproductive toxicity: Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test); Species: Rat; Result: NOAEL = 100 mg/kg; Literature information: ECHA Dossier; Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rat; Result: NOAEL = 5000 mg/kg; Literature information: ECHA Dossier

### 4,4'-methylenediphenyl diisocyanate, isomers and homologues

In vitro mutagenicity/genotoxicity: Method: EU Method B.13/14 (Mutagenicity - Reverse Mutation Test Using Bacteria) Result / evaluation: negative.; In vivo mutagenicity/genotoxicity Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test). Species: Rat. Result / evaluation: negative.; Carcinogenicity: Method: OECD 453. Species: Rat. Exposure duration: 2 years Result / evaluation: NOAEC = 0,2 mg/m³ Air.; Developmental toxicity/teratogenicity: Method: OECD 414. Species: Rat. Result / evaluation: NOAEC = 4 mg/m³ Air. Literature information: ECHA Dossier

### STOT-single exposure

May cause respiratory irritation. (4,4'-methylenediphenyl diisocyanate, isomers and homologues)

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (4,4'-methylenediphenyl diisocyanate, isomers and homologues)

alkanes, C14-17, chloro; chlorinated paraffins, C14-17:

Subchronic oral toxicity:

Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Species: Rat

Exposure duration: 90d Result: NOAEL = 100 mg/kg

Literature information: ECHA Dossier

# 4,4´-methylenediphenyl diisocyanate, isomers and homologues

Chronic inhalation toxicity: Method: OECD 453. Species: Rat. Exposure duration: 2 years Result / evaluation:

NOAEC = 0,2 mg/m³ Air. Literature information: ECHA Dossier

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Specific effects in experiment on an animal

No information available.

#### 11.2. Information on other hazards

# **Endocrine disrupting properties**

No information available.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

The product has not been tested.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17							
	Acute fish toxicity	LC50 mg/l	> 10000	96 h	Alburnus alburnus	Publication (1979)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	> 3,2		Pseudokirchneriella subcapitata	Study report (1997)	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	0,008	48 h	Daphnia magna	Study report (1996)	OECD Guideline 202	



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 11 of 16

	Fish toxicity	NOEC	5,6 mg/l	60 d	Oncorhynchus mykiss	Study report (1983)	OECD Guideline 204
	Crustacea toxicity	NOEC mg/l	0,01	21 d	Daphnia magna	Study report (1997)	other: OECD Guideline 202
115-10-6	dimethyl ether						
	Acute fish toxicity	LC50 mg/l	> 4100	96 h	Poecilia reticulata	ECHA Dossier	NEN 6504 Water - Determination of
	Acute algae toxicity	ErC50 mg/l	154,917	96 h	green algae	ECHA Dossier	Data generated using ECOSAR v1.00
	Acute crustacea toxicity	EC50 mg/l	> 4400	48 h	Daphnia magna	ECHA Dossier	NEN6501: Water -Determination of
25322-69-4	Propane-1,2-diol, propoxy	lated					
	Acute fish toxicity	LC50 mg/l	>100	96 h	Danio rerio	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Desmodesmus subspicatus	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna	ECHA Dossier	
	Crustacea toxicity	NOEC	(10) mg/l	21 d	Daphnia magna	ECHA Dossier	

# 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation	-			
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17				
	OECD Guideline 301 D	5%	28	ECHA Dossier	
	Not easily bio-degradable (according to OECD-criteria).				
9016-87-9	4,4´-methylenediphenyl diisocyanate, isomers and homologues				
	OECD 302	0%	28		
	Not easily bio-degradable (according to OECD-criteria).				
115-10-6	dimethyl ether				
	OECD 301D / EEC 92/69 annex V, C.4-E	5%	28	ECHA Dossier	
	Not easily bio-degradable (according to OECD-criteria).				
25322-69-4	Propane-1,2-diol, propoxylated				
	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	86,6%	28	ECHA Dossier	
	Readily biodegradable (according to OECD criteria).				

# 12.3. Bioaccumulative potential

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17	>= 4,7
115-10-6	dimethyl ether	0,07
25322-69-4	Propane-1,2-diol, propoxylated	-0,68 - 0,01

# BCF

CAS No	Chemical name	BCF	Species	Source
85535-85-9	alkanes, C14-17, chloro; chlorinated paraffins, C14-17	1087	Oncorhynchus mykiss	Study report (2000)

# 12.4. Mobility in soil

No information available.



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 12 of 16

#### 12.5. Results of PBT and vPvB assessment

The mixture contains the following substances fulfilling the PBT-/vPvB criteria according to REACH Annex XIII: Decamethylcyclopentasiloxane, Dodecamethylcyclohexasiloxane, Octamethylcyclotetrasiloxane

#### 12.6. Endocrine disrupting properties

No information available.

#### 12.7. Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

## Disposal recommendations

Dispose of waste according to applicable legislation.

Non-contaminated packages may be recycled.

According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

#### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances: hazardous waste

# List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

#### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity:

Excepted quantity:

Transport category:

Tunnel restriction code:

D

### Inland waterways transport (ADN)



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 13 of 16

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant: YES

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes







according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 14 of 16

Danger releasing substance: alkanes, C14-17, chloro; chlorinated paraffins, C14-17

#### 14.6. Special precautions for user

Refer to section 6-8

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 56

2010/75/EU (VOC): 21,3% 2004/42/EC (VOC): 209 g/I

Information according to 2012/18/EU

E1 Hazardous to the Aquatic Environment

(SEVESO III):

Additional information: P3a

#### Additional information

Aerosol directive (75/324/EEC)

UK REACH Appendix XVII, No (mixture): 3, 28, 40, 56.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of

child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

Rev. 1.00; 02.06.2015, Initial release

Rev. 2.0; 28.05.2018, Changes in chapter: 1-16. Rev. 3.0; 04.08.2021, Changes in chapter: 1-16.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EINECS: European Inventory of Existing Commercial chemical Substances

ELINCS: European LIst of Notified Chemical Substances

ECHA: European Chemicals Agency EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)



according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 15 of 16

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe

**UN: United Nations** 

VOC: Volatile Organic Compounds

### Classification for mixtures and used evaluation method according to GB CLP Regulation

one of the state o				
Classification procedure				
On basis of test data				
Bridging principle "Aerosols"				
Bridging principle "Aerosols"				
Bridging principle "Aerosols"				
Bridging principle "Aerosols"				
Calculation method				
Calculation method				
Bridging principle "Aerosols"				
Bridging principle "Aerosols"				
Calculation method				
Calculation method				

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.





according to UK REACH Regulation

# Montageschaum LORENCIC LO-FOAM 1K 750ml

Revision date: 04.08.2021 Product code: ZKR13LO Page 16 of 16

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking. EUH204 Contains isocyanates. May produce an allergic reaction.

### **Further Information**

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)